English | Construction telehandlers | MT

# MT 1335 75D ST5

## MACHINE BOOK

MANITOU
HANDLING YOUR WORLD

| Capacities | | Metric |
|---|---|---|
| Max. capacity | Q | 3500 kg |
| Max. lifting height | | 12.60 m |
| Max. outreach | | 8.65 m |
| Breakout force with bucket | | 7400 daN |
| **Weight and dimensions** | | |
| Overall length to carriage | l11 | 5.72 m |
| Length to face of forks | l2 | 5.72 m |
| Overall length (with forks) | l1 | 6.92 m |
| Overall width | b1 | 2.28 m |
| Overall height | h17 | 2.48 m |
| Wheelbase | y | 2.80 m |
| Ground clearance | m4 | 0.42 m |
| Overall cab width | b4 | 0.95 m |
| Tilt-up angle | a4 | 13 ° |
| Tilt-down angle | a5 | 114 ° |
| External turning radius | Wa3 | 3.78 m |
| External turning radius (over tyres) | Wa1 | 3.78 m |
| Unladen weight (with forks) | | 9470 kg |
| Overall weight | | 9470 kg |
| Tires type | | Inflatable |
| Standard tires | | Alliance 400/80 - 24 - 162A8 |
| Forks length / width / section | l / e / s | 1200 mm x 100 mm x 50 mm |
| **Performances** | | |
| Lifting | | 10.30 s |
| Lowering | | 9.60 s |
| Extension | | 14.70 s |
| Retraction | | 9.90 s |
| Crowd | | 3.20 s |
| Dump | | 3.80 s |
| **Engine** | | |
| Engine brand | | Deutz |
| Engine norm | | Stage V |
| Engine model | | TCD 2.9L |
| Number of cylinders / Capacity of cylinders | | 4 - 2924 cm³ |
| Engine power (Hp/kW) | | 75 Hp / 55.40 kW |
| Max. torque / Engine rotation | | 375 Nm @ 1400 rpm |
| Drawbar pull (Laden) | | 9700 daN |
| HVO validated (according to EN 15940 standard) | | Yes |
| **Electric circuit** | | |
| 12V Battery capacity | | 110 Ah |
| **Transmission** | | |
| Transmission type | | Torque converter |
| Number of gears (forward / reverse) | | 2 / 2 |
| Max. travel speed | | 24.90 km/h |
| Parking brake | | Mechanical foot-operated parking brake |
| Service brake | | Hydraulic servo brake |
| **Hydraulics** | | |
| Hydraulic pump type | | Axial piston |
| Hydraulic flow / Pressure | | 133 l/min-260 bar |
| **Tank capacities** | | |
| Engine oil | | 8.50 l |
| Hydraulic oil | | 153 l |
| Fuel tank capacity | | 137 l |
| **Noise and vibration** | | |
| Noise at driving position (LpA) | | 77 dB |
| Noise to environment (LwA) | | 104 dB |
| Vibration on hands/arms | | < 2.50 m/s² |
| **Miscellaneous** | | |
| Steering wheels (front / rear) | | 2 / 2 |
| Drive wheels (front / rear) | | 2 / 2 |
| Safety / Cab certification | | Standard EN 15000 / Cabin ROPS - FOPS level 2 |
| Controls | | JSM |












Machine on tires with forks Metric




Machine on lowered stabilisers with forks Metric



BUCKETS

# Big Bag Filling Bucket

## Big Bag Filling Bucket - BBF 1200 / 600

| Reference number | Heaped capacity | Overall weight | Overall height | Overall length | Width |
|---|---|---|---|---|---|
| 52676645 | 600 l | 455 kg | 685 mm | 1549 mm | 1200 mm |

**Mandatory machine equipment:**

## Big Bag Filling Bucket - BBF 1400 / 1100

| Reference number | Heaped capacity | Overall weight | Overall height | Overall length | Width |
|---|---|---|---|---|---|
| 52614700 | 1120 l | 610 kg | 923 mm | 1723 mm | 1400 mm |

**Mandatory machine equipment:**

BUCKETS

# Bucket 4 in 1

## Bucket 4 in 1 - CB4x1 850L / 2300

| Reference number | Distance to center of gravity | Capacity | Heaped capacity | Struck capacity | Overall weight |
|---|---|---|---|---|---|
| 751401 | 374 mm | 1783 kg | 849 l | 628 l | 682 kg |
| **Overall height** | **Overall length** | **Width** | | | |
| 890 mm | 1107 mm | 2300 mm | | | |

**Mandatory machine equipment:**

## Bucket 4 in 1 - CB4x1 900L / 2450

| Reference number | Distance to center of gravity | Capacity | Heaped capacity | Struck capacity | Overall weight |
|---|---|---|---|---|---|
| 751465 | 380 mm | 1888 kg | 899 l | 672 l | 714 kg |
| **Overall height** | **Overall length** | **Width** | | | |
| 890 mm | 1110 mm | 2450 mm | | | |

**Mandatory machine equipment:**

BUCKETS

## Concrete Mixing Bucket

### Concrete Mixing Bucket - BMC 500

| Reference number | Capacity | Overall weight | Overall height | Width | Depth |
|---|---|---|---|---|---|
| 52728343 | 500 kg | 770 kg | 1050 mm | 1950 mm | 1050 mm |

**Mandatory machine equipment:** + 

BUCKETS

## Construction Bucket

### Construction Bucket - CBC 800L / 2250

| Reference number | Distance to center of gravity | Capacity | Heaped capacity | Struck capacity | Overall weight |
|---|---|---|---|---|---|
| 654471 | 355 mm | 1709 kg | 814 l | 666 l | 366 kg |
| **Overall height** | **Overall length** | **Width** | | | |
| 810 mm | 1026 mm | 2250 mm | | | |

**Mandatory machine equipment:**

### Construction Bucket - CBC 900L / 2450

| Reference number | Distance to center of gravity | Capacity | Heaped capacity | Struck capacity | Overall weight |
|---|---|---|---|---|---|
| 654470 | 365 mm | 1875 kg | 893 l | 728 l | 391 kg |
| **Overall height** | **Overall length** | **Width** | | | |
| 810 mm | 1026 mm | 2450 mm | | | |

**Mandatory machine equipment:**

BUCKETS

## General Purpose Bucket

### General Purpose Bucket - CBR 900 / 2250

| Reference number | Reference number E-RECO | Capacity | Heaped capacity | Struck capacity | Overall weight |
|---|---|---|---|---|---|
| 653749 | 921281 | 1898 kg | 904 l | 736 l | 360 kg |
| **Overall height** | **Overall length** | **Width** | | | |
| 775 mm | 815 mm | 2250 mm | | | |

**Mandatory machine equipment:**

## General Purpose Bucket - CBR 1000 / 2450

| Reference number | Reference number with bolted wearplate (WP) | Capacity | Heaped capacity | Struck capacity | Overall weight |
|---|---|---|---|---|---|
| 654716 | 52000370 | 2079 kg | 990 l | 804 l | 381 kg |
| **Overall height** | **Overall length** | **Width** | | | |
| 775 mm | 815 mm | 2450 mm | | | |

**Mandatory machine equipment:** ✕

BUCKETS

# General Purpose Bucket Essential

## General Purpose Bucket Essential - BGP 2000 / 800 Essential

| Reference number | Distance to center of gravity | Capacity | Heaped capacity | Struck capacity | Overall weight |
|---|---|---|---|---|---|
| 52688160 | 425 mm | 1684 kg | 802 l | 622 l | 345 kg |
| **Overall height** | **Overall length** | **Width** | **Depth** | | |
| 786 mm | 925 mm | 2000 mm | 817 mm | | |

**Mandatory machine equipment:** ✕

## General Purpose Bucket Essential - BGP 2300 / 900 Essential

| Reference number | Distance to center of gravity | Capacity | Heaped capacity | Struck capacity | Overall weight |
|---|---|---|---|---|---|
| 52690756 | 429 mm | 1955 kg | 931 l | 718 l | 379 kg |
| **Overall height** | **Overall length** | **Width** | **Depth** | | |
| 786 mm | 975 mm | 2300 mm | 817 mm | | |

**Mandatory machine equipment:** ✕

## General Purpose Bucket Essential - BGP 2450 / 1000 Essential

| Reference number | Distance to center of gravity | Capacity | Heaped capacity | Struck capacity | Overall weight |
|---|---|---|---|---|---|
| 52658055 | 434 mm | 2089 kg | 995 l | 766 l | 397 kg |
| **Overall height** | **Overall length** | **Width** | **Depth** | | |
| 786 mm | 925 mm | 2450 mm | 817 mm | | |

**Mandatory machine equipment:** ✕

ON FORK HANDLING SOLUTIONS

## Carriage Floating Load Backrest And Forks (MT - MLT)

### Carriage Floating Load Backrest And Forks (MT - MLT) - CAF 1040 / 4100 LB

| Reference number | Distance to center of gravity | Capacity | Overall weight | Overall height | Overall length |
|---|---|---|---|---|---|
| 52866338 | 271 mm | 4100 kg | 335 kg | 1036 mm | 1514 mm |

| Width |
|---|
| 1160 mm |

**Mandatory machine equipment:**

### Carriage Floating Load Backrest And Forks (MT - MLT) - CAF 1300 / 4100 LB

| Reference number | Distance to center of gravity | Capacity | Overall weight | Overall height | Overall length |
|---|---|---|---|---|---|
| 52866340 | 271 mm | 4100 kg | 363 kg | 1036 mm | 1514 mm |

| Width |
|---|
| 1420 mm |

**Mandatory machine equipment:**

ON FORK HANDLING SOLUTIONS

## Floating Fork Carriage With Side Shift (MT)

### Floating Fork Carriage With Side Shift (MT) - TFF 35 DL 1040

| Capacity | Width |
|---|---|
| 3500 kg | 1040 mm |

**Mandatory machine equipment:**

ON FORK HANDLING SOLUTIONS

## Hydraulic Floating Fork Positioner

### Hydraulic Floating Fork Positioner - CAF 1260 / 4500 P

| Distance to center of gravity | Capacity | Overall weight | Overall height | Overall length | Forks section X Forks width X Forks length |
|---|---|---|---|---|---|
| 305 mm | 4500 kg | 350 kg | 1184 mm | 1532 mm | 50 mm X 100 mm X 1200 mm |

| Width |
|---|
| 1303 mm |

**Mandatory machine equipment:**

ON FORK HANDLING SOLUTIONS

# Tilting Forks Carriage

## Tilting Forks Carriage - PFB 35N 1260

| Reference number | Capacity | Overall weight | Width |
|---|---|---|---|
| 653744 | 3500 kg | 93 kg | 1302 mm |

**Mandatory machine equipment:** ✕

## Tilting Forks Carriage - PFB 35N 1470

| Reference number | Capacity | Overall weight | Width |
|---|---|---|---|
| 653745 | 3500 kg | 117 kg | 1512 mm |

**Mandatory machine equipment:** ✕

## Tilting Forks Carriage - PFB 35N 1580

| Reference number | Capacity | Overall weight | Width |
|---|---|---|---|
| 653746 | 3500 kg | 122 kg | 1622 mm |

**Mandatory machine equipment:** ✕

ON FORK HANDLING SOLUTIONS

# Tilting Forks Carriage With Load Backrest (MLT - MT)

## Tilting Forks Carriage With Load Backrest (MLT - MT) - PFB 35N 1260 LB

| Capacity | Overall weight | Overall height | Width |
|---|---|---|---|
| 3500 kg | 130 kg | 1185 mm | 1284 mm |

**Mandatory machine equipment:** ✕

### Tilting Forks Carriage With Load Backrest (MLT - MT) - PFB 35N 1470 LB

| Capacity | Overall weight | Overall height | Width |
|---|---|---|---|
| 3500 kg | 158 kg | 1185 mm | 1494 mm |

**Mandatory machine equipment:** ✕

ON FORK HANDLING SOLUTIONS

## Tilting Forks Carriage With Side Shift (MLT - MT)

### Tilting Forks Carriage With Side Shift (MLT - MT) - PFB 35N 1260 SS

| Capacity | Overall weight | Overall height | Width |
|---|---|---|---|
| 3500 kg | 175 kg | 658 mm | 1260 mm |

**Mandatory machine equipment:**

### Tilting Forks Carriage With Side Shift (MLT - MT) - PFB 35N 1580 SS

| Capacity | Overall weight | Overall height | Width |
|---|---|---|---|
| 3500 kg | 300 kg | 658 mm | 1580 mm |

**Mandatory machine equipment:**

ON FORK HANDLING SOLUTIONS

## Tilting Forks Carriage With Side Shift - Load Backrest (MLT - MT)

### Tilting Forks Carriage With Side Shift - Load Backrest (MLT - MT) - PFB 35N 1260 SS LB

| Capacity | Overall weight | Overall height | Width |
|---|---|---|---|
| 3500 kg | 210 kg | 1229 mm | 1284 mm |

**Mandatory machine equipment:**

JIBS

## 2-Hook Jib

### 2-Hook Jib - P 4000

| Reference number | Reference number E-RECO | Distance to center of gravity | Capacity | Capacity 2 | Overall weight |
|---|---|---|---|---|---|
| 653226 | 921321 | 785 mm | 4000 kg | 1200 kg | 210 kg |
| **Max. outreach** | **Maximum outreach 2** | **Overall length** | **Width** | | |
| 708 mm | 2708 mm | 2838 mm | 830 mm | | |

**Mandatory machine equipment:** ✕

JIBS

## Big Bag Handler

### Big Bag Handler - HBB 1500 / 2400

| Reference number | Reference number E-RECO | Skid Steer Carriage reference | 4 point Carriage | Euro Carriage | Distance to center of gravity |
|---|---|---|---|---|---|
| 52781808 | 931627 | 52578030 | 52742058 | 52742059 | 388 mm |
| **Capacity** | **Overall weight** | **Overall height** | **Overall length** | **Forks spread** | **Width** |
| 2400 kg | 186 kg | 1322 mm | 1643 mm | 750 mm | 1356 mm |

**Mandatory machine equipment:** ✕

JIBS

## Extensible Jib

### Extensible Jib - JE 6000 / 600

| Reference number | Distance to center of gravity | Capacity | Capacity 2 | Capacity 3 | Overall weight |
|---|---|---|---|---|---|
| 939995 | 1516 mm | 600 kg | 300 kg | 100 kg | 265 kg |
| **Max. outreach** | **Maximum outreach 2** | **Maximum outreach 3** | **Overall length** | **Width** | |
| 3895 mm | 4845 mm | 5845 mm | 4347 mm | 815 mm | |

**Mandatory machine equipment:** ✕

JIBS

## Extension Jib

### Extension Jib - P 600

| Reference number | Reference number E-RECO | Capacity | Overall weight | Max. outreach | Overall height |
|---|---|---|---|---|---|
| 653228 | 921316 | 600 kg | 210 kg | 3746 mm | 990 mm |
| **Overall length** | **Width** | | | | |
| 3947 mm | 830 mm | | | | |

**Mandatory machine equipment:** ✕

JIBS

# Frame Mounted Hook

## Frame Mounted Hook - PC 50

| Reference number | Reference number E-RECO | Distance to center of gravity | Capacity | Overall weight | Max. outreach |
|---|---|---|---|---|---|
| 708544 | 921335 | 166 mm | 5000 kg | 115 kg | 470 mm |
| **Overall height** | **Overall length** | **Width** | | | |
| 500 mm | 606 mm | 815 mm | | | |

**Mandatory machine equipment:** ✕

JIBS

# Swing Jib

## Swing Jib - PO 600 / 2500

| Reference number | Distance to center of gravity | Capacity | Overall weight | Max. outreach | Overall height |
|---|---|---|---|---|---|
| 784641 | 720 mm | 600 kg | 320 kg | 2500 mm | 842 mm |
| **Overall length** | **Width** | | | | |
| 2874 mm | 830 mm | | | | |

**Mandatory machine equipment:**

## Swing Jib - PO 1000 / 1500

| Reference number | Distance to center of gravity | Capacity | Overall weight | Max. outreach | Overall height |
|---|---|---|---|---|---|
| 784642 | 450 mm | 1000 kg | 275 kg | 1500 mm | 1056 mm |
| **Overall length** | **Width** | | | | |
| 1874 mm | 830 mm | | | | |

**Mandatory machine equipment:**

## Swing Jib - PO 2000 / 1000

| Reference number | Distance to center of gravity | Capacity | Overall weight | Max. outreach | Overall height |
|---|---|---|---|---|---|
| 784643 | 243 mm | 2000 kg | 255 kg | 1000 mm | 842 mm |
| **Overall length** | **Width** | | | | |
| 1374 mm | 830 mm | | | | |

**Mandatory machine equipment:**

SKIP

# Concrete Skip



## Concrete Skip - BB 500

| Reference number | Distance to center of gravity | Capacity | Heaped capacity | Overall weight | Overall height |
|---|---|---|---|---|---|
| 52000637 | 556 mm | 1200 kg | 500 l | 191 kg | 776 mm |
| Overall length | Width | | | | |
| 1466 mm | 1216 mm | | | | |

**Mandatory machine equipment:** ✕



## Concrete Skip - BBG 500

| Reference number | Distance to center of gravity | Capacity | Heaped capacity | Overall weight | Overall height |
|---|---|---|---|---|---|
| 52000639 | 598 mm | 1200 kg | 500 l | 201 kg | 776 mm |
| Overall length | Width | | | | |
| 1466 mm | 1220 mm | | | | |

**Mandatory machine equipment:** ✕



## Concrete Skip - BBH 500

| Reference number | Distance to center of gravity | Capacity | Heaped capacity | Overall weight | Overall height |
|---|---|---|---|---|---|
| 52000638 | 578 mm | 1200 kg | 500 l | 200 kg | 776 mm |
| Overall length | Width | | | | |
| 1466 mm | 1110 mm | | | | |

**Mandatory machine equipment:**



## Concrete Skip - BBHG 500

| Reference number | Distance to center of gravity | Capacity | Heaped capacity | Overall weight | Overall height |
|---|---|---|---|---|---|
| 52000640 | 618 mm | 1200 kg | 500 l | 210 kg | 776 mm |
| Overall length | Width | | | | |
| 1466 mm | 1110 mm | | | | |

**Mandatory machine equipment:**

SKIP

## Crane Skip

### Crane Skip - GL 600

| Reference number | Reference number E-RECO | Distance to center of gravity | Capacity | Heaped capacity | Overall weight |
|---|---|---|---|---|---|
| 52000528 | 52000528 | 465 mm | 1440 kg | 600 l | 227 kg |
| **Overall height** | **Overall length** | **Width** | | | |
| 1197 mm | 995 mm | 1361 mm | | | |

**Mandatory machine equipment:** ✕

### Crane Skip - GL 600 H

| Reference number | Reference number E-RECO | Distance to center of gravity | Capacity | Heaped capacity | Overall weight |
|---|---|---|---|---|---|
| 52000529 | 52553617 | 443 mm | 1440 kg | 600 l | 245 kg |
| **Overall height** | **Overall length** | **Width** | | | |
| 1197 mm | 995 mm | 1326 mm | | | |

**Mandatory machine equipment:**

SWEEPER & CLEANER

## Push broom



### Push broom - SCPB 2500

| Reference number | Overall weight | Overall height | Overall length | Width |
|---|---|---|---|---|
| 52804221 | 215 kg | 490 mm | 1040 mm | 2490 mm |

**Mandatory machine equipment:** ✕

SWEEPER & CLEANER

## Sweeper 2 in 1

### Sweeper 2 in 1 - SCC 2600

| Reference number | Overall weight | Overall height | Overall length | Width |
|---|---|---|---|---|
| 52000515 | 755 kg | 950 mm | 2140 mm | 2820 mm |

**Mandatory machine equipment:**

## Sweeper 2 in 1 - SCC 2600 +

| Reference number | Reference number E-RECO | Overall weight | Overall height | Overall length | Width |
|---|---|---|---|---|---|
| 52000517 | 52000517 | 730 kg | 950 mm | 2170 mm | 2820 mm |

**Mandatory machine equipment:**

## Sweeper 2 in 1 - SCC 2600 HWA +

| Reference number | Overall weight | Overall height | Overall length | Width |
|---|---|---|---|---|
| 52000519 | 800 kg | 1550 mm | 2170 mm | 2820 mm |

**Mandatory machine equipment:** +

WINCH RANGE

# Hydraulic Winch

## Hydraulic Winch - Winch 3T

| Reference number | Reference number E-RECO | Distance to center of gravity | Working height | Capacity | Overall weight |
|---|---|---|---|---|---|
| 885236 | 921337 | 320 mm | 24 m | 3000 kg | 310 kg |
| **Max. outreach** | **Overall height** | **Overall length** | **Cable** | **Width** | **Depth** |
| 519 mm | 1869 mm | 900 mm | 1 loop | 1080 mm | 763 mm |

**Mandatory machine equipment:** +

MISCELLANEOUS ATTACHMENTS

# Material Basket

## Material Basket - MB 2000 / 1000

| Reference number | Distance to center of gravity | Capacity | Overall weight | Overall height | Overall length |
|---|---|---|---|---|---|
| 52596600 | 694 mm | 1000 kg | 400 kg | 1215 mm | 1632 mm |
| **Width** | **Depth** | | | | |
| 2056 mm | 1120 mm | | | | |

**Mandatory machine equipment:**

**Head Office**
B.P. 249 - 430 rue de l'Aubinière
44150 Ancenis Cedex - France
Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97
www.manitou.com

This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.
MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes

**18_08_2026_10:29_MT_1335_75D_ST5_machine_book_EN**